

GRUPPI DI PRESSURIZZAZIONE A VELOCITA' FISSA

DUE POMPE CENTRIFUGHE BIGIRANTI

MODELLO POMPA

Elettropompe Pedrollo centrifughe bigiranti tipo 2CP:

- Corpo pompa in ghisa.
- Giranti in OTTONE.
- 2CP25/130 (HP 1.00) con giranti in acciaio inox AISI 304.



monofase	trifase	KW	HP	DN1	DN2
2CPm 25/130	2CP 25/130	0,75	1	1"1/4	1"
2CPm 25/14B	2CP 25/14B	1,1	1,5	1"1/4	1"
2CPm 25/16C	2CP 25/16C	1,1	1,5	1"1/4	1"
2CPm 25/16B	2CP 25/16B	1,5	2	1"1/4	1"
2CPm 25/14A	2CP 25/14A	1,5	2	1"1/4	1"
-	2CP 25/16A	2,2	3	1"1/4	1"
-	2CP 32/200C	3	4	1"1/2	1"1/4
-	2CP 32/200B	4	5,5	1"1/2	1"1/4
-	2CP 32/210B	5,5	7,5	2"	1"1/4
-	2CP 32/210A	7,5	10	2"	1"1/4
-	2CP 40/180C	4	5,5	2"	1"1/2
-	2CP 40/180B	5,5	7,5	2"	1"1/2
-	2CP 40/180A	7,5	10	2"	1"1/2

MODELLO	POTENZA		Q MAX 2 pompe m³/h	PREV. MAX metri	L mm B	W mm A	H mm C	PESO kg	COLLETTORI		ALIMENTAZIONE
	KW	HP							asp.	mand.	
GP 2CPm 25/130	2x0,75	2x1	12,0	42	746	540	690	52	1"1/2	1"1/2	monofase
GP 2CPm 25/14B	2x1,1	2x1,5	12,0	54	771	540	690	71	2"	1"1/2	monofase
GP 2CPm 25/16C	2x1,1	2x1,5	14,4	47	771	540	690	71	2"	1"1/2	monofase
GP 2CPm 25/16B	2x1,5	2x2	16,8	58	780	540	690	80	2"	1"1/2	monofase
GP 2CPm 25/14A	2x1,5	2x2	13,2	67	780	540	690	80	2"	1"1/2	monofase
GP 2CP 25/130	2x0,75	2x1	12,0	42	746	540	690	52	1"1/2	1"1/2	trifase
GP 2CP 25/14B	2x1,1	2x1,5	12,0	54	771	540	690	71	2"	1"1/2	trifase
GP 2CP 25/16C	2x1,1	2x1,5	14,4	47	771	540	690	71	2"	1"1/2	trifase
GP 2CP 25/16B	2x1,5	2x2	16,8	58	780	540	690	80	2"	1"1/2	trifase
GP 2CP 25/14A	2x1,5	2x2	13,2	67	780	540	690	80	2"	1"1/2	trifase
GP 2CP 25/16A	2x2,2	2x3	19,2	68	780	540	690	82	2"	1"1/2	trifase
GP 2CP 32/200C	2x3	2x4	30,0	70	982	750	690	112	2"1/2	2"1/2	trifase
GP 2CP 32/200B	2x4	2x5,5	30,0	85	982	750	690	118	2"1/2	2"1/2	trifase
GP 2CP 32/210B	2x5,5	2x7,5	30,0	94	987	750	690	149	2"1/2	2"1/2	trifase
GP 2CP 32/210A	2x7,5	2x10	30,0	112	987	750	690	156	2"1/2	2"1/2	trifase
GP 2CP 40/180C	2x4	2x5,5	42,0	64	1056	750	690	168	4"	3"	trifase
GP 2CP 40/180B	2x5,5	2x7,5	48,0	76	1056	750	690	178	4"	3"	trifase
GP 2CP 40/180A	2x7,5	2x10	48,0	88	1056	750	690	188	4"	3"	trifase

PRESTAZIONI IDRAULICHE

TIPO	POTENZA		Q	m³/h l/min	H metri																
	KW	HP			0	2,4	4,8	7,2	9,6	12	13,2	15	16,8	19,2	21,6	24	30	36	42	48	54
GP 2CP25/130	2x0,75	2x1		42	39	34	28,5	22	15												
GP 2CP25/14B	2x1,1	2x1,5		54	52	47,5	41	33	22												
GP 2CP25/16C	2x1,1	2x1,5		47	46	44	40	35	30	27	24										
GP 2CP25/16B	2x1,5	2x2		58	56	54	51	47	43	40	37	30									
GP 2CP25/14A	2x1,5	2x2		66	64	60	53	44	35	30											
GP 2CP25/16A	2x2,2	2x3		68	67	64,5	62	58	54	51	47	41	32								
GP 2CP32/200C	2x3	2x4		70	-	66,5	65	63	60,5	59	58	55	52	49,5	46,5	36					
GP 2CP32/200B	2x4	2x5,5		85	-	81	79	77	75	74	72	69	66	62	58	49					
GP 2CP32/210B	2x5,5	2x7,5		94	-	94	93	91	89	87	86	83	79	75	70	56					
GP 2CP32/210A	2x7,5	2x10		112	-	111	110,5	110	108	107	105	102	99	94	89	74					
GP 2CP40/180C	2x4	2x5,5		64	-	-	-	-	62	61,3	60,1	59	57,5	56	54,5	49	43	35			
GP 2CP40/180B	2x5,5	2x7,5		76	-	-	-	-	73	72,5	71,8	71	70	69	67,5	64	59,5	54	46		
GP 2CP40/180A	2x7,5	2x10		88	-	-	-	-	85	84,5	83,8	83	82	81	79,5	76	72	67	60		
GP 2CP40/200B	2x9,2	2x12,5		97	-	-	-	-	94	93,5	92,8	92	91	90	88	85	80	74	68	61	
GP 2CP40/200A	2x11	2x15		105	-	-	-	-	102	101,5	100,8	100	99	98	97	93	88	83	76	69	